

Cut Noise & Exhaust Gas,
With Electric-Motor Drive
Deliver a comfortable working space even in the greenhouse



New

Electric Boom Lift HE350

★ Work with electricity

- The machine can be operated for about 2 days in field work with a full charge of battery.
(Continuous operating time at full charge : 3 to 3.5 hours)
- It is possible to charge from a household electric outlet.
(Charging time is 12 to 14 hours for full charge.)

★ Easy operation

- You can operate the travel lever by one hand for going forward, backward, and turning. Pivot turning is also possible, demonstrate high driving force in the field.
- Boom up / down and turning operations can be performed with a single lever.



★ 3 Safety equipment

- ① **Overload warning device**
When the loading capacity exceeds 100 kg, it warns with a buzzer and a lamp, and the boom stops rising.
- ② **Falling over prevention device**
A warning is given by a buzzer and a lamp when the inclination exceeds 10°, and the machine stops traveling.
- ③ **Emergency stop button**
All the functions stop when pressing the button.

★ Quietness

- Possible to work comfortably while listening to music and radio.



HE350 Specifications

Dimensions	L x W x H (mm)	3315 × 1300 × 1260	Travel Section	Speed Change	Variable change without steps
	Weight (kg)	755		Speed	Forward (km/h)
Platform	Floor W x L (mm)	645 x 550			Backward (km/h)
	Loading Capacity (kg)	100		Crawler Width x Bearing	180 x 1320 (mm)
	Floor Height (mm)	260 - 3500		Track (mm)	1120
	Outside Moving Range (mm)	3560 (When the boom is horizontal)		Control System	Individual motors on right and left
	Turning Angle	27° to right and left			

*The specifications are subject to change without notice.

FUJII Fujii Corporation Co., Ltd.

Address

285 Koike, Tsubame City, Niigata Prefecture, Japan
<https://www.e-fujii.co.jp/eng/index.html>

